

90° Rigid Twist Waveguide



90° Rigid Twist Waveguide

Frequency Range: 2.60GHz ~ 110GHz

Model: WR284 ~ WR10

Customised orders are welcomed.

Technical Data:

Model No.	E.I.A	Freq(GHz)	Flange	VSWR	Normal length in (mm)	Weight oz (g)
HX-RTW90-90°	WR90	8.2-12.4	UG39/U	1.10	5.5 (140)	-
HX-RTW75-90°	WR75	10.0-15.0	UBR120	1.10	5.0 (125)	5.5 (156)
HX-RTW62-90°	WR62	12.4-18.0	UG419/U	1.10	4.0 (100)	4.0 (113)
HX-RTW42-90°	WR42	18.0-26.5	UG595/U	1.10	3.0 (75)	1.7 (48)
HX-RTW34-90°	WR34	21.7-33.0	UG1530/U	1.10	3.0 (75)	1.5 (45)
HX-RTW28-90°	WR28	26.5-40.0	UG599/U	1.10	3.0 (75)	1.2 (34)
HX-RTW22-90°	WR22	33.0-50.0	UG383/U	1.10	2.8 (70)	1.1 (30)
HX-RTW19-90°	WR19	40.0-60.0	UG383/UM	1.10	(50)2.0	1.6 (45)
HX-RTW15-90°	WR15	50.0-75.0	UG385/U	1.10	(45)1.7	1.0 (28)
HX-RTW12-90°	WR12	60.0-90.0	UG387/U	1.10	(45)2.0	1.0 (28)
HX-RTW10-90°	WR10	75.0-110.0	UG387/UM	1.10	(45)2.0	0.9 (25)